



# Remote Cargo Hook Test Form

## C15

Work Order \_\_\_\_\_

Customer \_\_\_\_\_

Serial Number \_\_\_\_\_

Date \_\_\_\_\_

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/fail
1	37,500	Static Hold	Hold for two Minutes and reduce load to zero	N/A	
10	7,500	Electircal, 25 volts	No "hang ups" permitted	N/A	
2	15,000	Electircal, 22 volts	Current shall not exceed 12.4A	Amp.	
2	11,250	Electircal, 22 volts	Current shall not exceed 12.4A	Amp.	
2	7,500	Electircal, 22 volts	Current shall not exceed 12.4A	Amp.	
2	3,750	Electircal, 22 volts	Current shall not exceed 12.4A	Amp.	
2	500	Electircal, 22 volts	Current shall not exceed 12.4A	Amp.	
1	15,000	Electircal, 20 volts	Current shall not exceed 11.3A	Amp.	
1	15,000	Electircal, 28 volts	Current shall not exceed 15.8A	Amp.	
1	15,000	Manual		N/A	
1	15,000	Impact Test	Impact shackle 10 times, shall not release	N/A	
1	N/A	Solenoid Ohms	Shall not exceed 1.7-2.0Ohms	Ohms	
1	N/A	Electircal Continuity	Across both wires	N/A	

Test Conducted By:

Signature: \_\_\_\_\_

Technician

QC 5 Small FAB / QA